

## Huntley Community School District 158

October 19, 2015

### Addendum No. 2 to Bid Specification for Replacement of Floor Finish Bid #2015-15a

To All Bidders:

Following is **Addendum No. 2** to the Bid Specification for **Replacement of Floor Finish Bid #2015-15a** for Huntley Community School District 158. Please acknowledge the addendum on your bid form. The due date for bids remains the same; 2:30 p.m. on October 23, 2015. Please use the revised page one of the bid form with putting together your bid packet in the place of the page one version in the bid specification. However, do provide all other bid forms in the original bid specification for a complete bid. We look forward to seeing you at the bid opening.

Respectfully,

Doug Renkosik  
Director of O&M

#### **ITEMS TO BE INCLUDED AS A PART OF ADDENDUM NO. 2 ARE:**

1. Carpet to be installed on stairs in the E1311 as a part of the bid shall be sheet goods meeting the attached specification.

# Interface

## Cubic

Sheet Goods

PRODUCT NUMBER: 1380109700  
 PRODUCT CONSTRUCTION: Tufted Textured Loop  
 STANDARD COLORLINE: 18

YARN SYSTEM: 100% Recycled Content Type 6 Nylon  
 YARN MANUFACTURER: Aquafil  
 DYE METHOD: 100% Solution Dye

RECYCLED CONTENT:  
 Post Industrial Range: 5% - 9%  
 Post Consumer: 2%  
 Total Recycled Content: 7% - 11%

SOIL/STAIN PROTECTION: Protekt<sup>2</sup>@  
 ANTIMICROBIAL: (AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

PRODUCT SPECIFICATIONS	U.S.	METRIC
TUFTED YARN WEIGHT:	18 oz/yd <sup>2</sup>	610.0 g/m <sup>2</sup>
MACHINE GAUGE:	1/12 in	47.2 ends/10 cm
PILE HEIGHT:	0.145 in	3.7 mm
PILE THICKNESS:	0.093 in	2.4 mm
STITCHES:	8.16 /in	32.13 ends/10 cm
PILE DENSITY:	6968	
TOTAL THICKNESS:	0.181 in	4.5974 mm
SIZE:	78.74 in	2 m

## PERFORMANCE SPECIFICATIONS

Radiant Panel: (ASTM E-648) Class 1  
 Smoke Density: (ASTM E - 662) ≤450  
 Lightfastness: (AATCC 16 - E) ≥ 4.0 @ 60 AFU's  
 Static: (AATCC - 134) < 3.0 KV  
 Standard Backing: GlasBac® Tile(50 cm x 50 cm)  
 Backing Options: Sheet Goods(2 m), GlasBac® Tile(50 cm x 50 cm), NexStep® Tile(50 cm x 50 cm), GlasBac® RE Tile(50 cm x 50 cm)

## INSTALLATION

Tile: Non-Directional

All Product Specifications are averages derived from product sample testing and are subject to normal manufacturing tolerances and testing tolerances. "Tufted Yarn Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting and shearing will result in a lower finished yarn weight in purchased carpet. Pile Density stated in the Product Specifications is based on the Tufted Yarn Weight. Product Specifications may be changed without notice as long as product performance is not materially affected.

Issue Date:11/3/04